

Selection and ordering data

Article No.

Article No.

Milltronics WD600

A low- to medium- capacity scale for light to medium belt loading.
304 stainless steel construction with Delrin sliders. Load cells are available in nickel plated, or stainless steel. Two calibration weights are required and are ordered as separate line item. Refer to Calibration weights.

↗ Click on the Article No. for the online configuration in the PIA Life Cycle Portal.

Belt width

12 inch (300 mm)
18 inch (450 mm)
24 inch (600 mm)
30 inch (750 mm)
36 inch (900 mm)
42 inch (1 000 mm)
48 inch (1 200 mm)

Load cell capacity

Nickel plated

10 kg (22 lb)
15 kg (33.1 lb)
20 kg (44 lb)
30 kg (66.2 lb)
50 kg (110 lb)

Stainless steel

6 kg (13.2 lb)
12 kg (26.4 lb)
30 kg (66.2 lb)

Further designs

Please add **"-Z"** to article no. and specify order code(s).

Stainless steel tag [69 x 38 mm (2.7 x 1.5 inch)], Measuring-point number / identification (max 27 characters), specify in plain text.

Application Eng. reference number (max. 15 characters), specify in plain text.

Manufacturer's test certificate:
According to EN 10204-2.2

7MH7185-

A0

1
2
3
4
5
6
7

D
E
F
G
L
H
J
K

Order Code

Y15

Y31

C11

Operating instructions

- English
- German

Belt Scale Application Guidelines

- English
- French
- German
- Spanish

Note: the operating instructions should be ordered as a separate line on the order.

All literature is available to download for free, in a range of languages, at

<http://www.siemens.com/processinstrumentation/documentation>

This device is shipped with the Siemens Level and Weighing manual DVD containing the complete operating instructions library.

Spare parts

Load cells

Stainless steel

6 kg (13.2 lb)
12 kg (26.4 lb)
30 kg (66.2 lb)

Nickel plated

10 kg (22 lb)
15 kg (33.1 lb)
20 kg (44 lb)
30 kg (66.2 lb)
50 kg (110 lb)

Slider bar middle UHMW PE (for old style WD600)

Slider bar side UHMW PE (for old style WD600)

Slider bar acetal

Test chain 1.62 lb/ft (2.41 kg/m), 60 inch

Calibration Hanger Weights

200 g (0.4 lb)
500 g (1.1 lb)
1 000 g (2.2 lb)
2 000 g (4.4 lb)
3 500 g (7.7 lb)
5 000 g (11 lb)
7 500 g (16.5 lb)
8 500 g (18.7 lb)
10 000 g (22 lb)
12 000 g (26.5 lb)
15 000 g (33.1 lb)

Note: calibration accessories should be ordered as a separate item on the order.

7ML1998-5KM03
A5E32015601

7ML1998-5GA01
7ML1998-5GA11
7ML1998-5GA31
7ML1998-5GA21

7MH7725-1EG
7MH7725-1EH
7MH7725-1EJ

7MH7725-1EK
7MH7725-1EL
7MH7725-1EM
7MH7725-1EN
7MH7725-1EP

7MH7723-1KF
7MH7723-1KE
7MH7723-1KG
7MH7723-1NF

7MH7724-1AF
7MH7724-1AG
7MH7724-1AH
7MH7724-1AJ
7MH7724-1BQ
7MH7724-1AK
7MH7724-1BR
7MH7724-1BS
7MH7724-1BT
7MH7724-1BU
7MH7724-1BV