

Milltronics test chain storage reels

7MH7163-

Test chain storage reels are used to store roller test chains. All test chain storage reels come with a geared brake motor.

↗ Click on the Article No. for the online configuration in the PIA Life Cycle Portal.

Compartment size

- 5 inch (127 mm) for chain sizes: 5 lb/ft (7.4 kg/m), 10 lb/ft (14.9 kg/m) **0**
- 6 inch (152 mm) for chain sizes: 7.5 lb/ft (11.2 kg/m) **1**
- 7 inch (178 mm) for chain sizes: 15 lb/ft (22.3 kg/m), 20 lb/ft (29.8 kg/m), 25 lb/ft (37.2 kg/m) **2**
- 8 inch (203 mm) for chain sizes: 30 lb/ft (44.6 kg/m), 35 lb/ft (52.1 kg/m) **3**
- 11 inch (279 mm) for chain sizes: 40 lb/ft (59.5 kg/m), 45 lb/ft (67.0 kg/m), 50 lb/ft (74.4 kg/m) **4**
- 12 inch (305 mm) for chain sizes: 55 lb/ft (81.9 kg/m), 60 lb/ft (89.3 kg/m) **5**
- 13 inch (330 mm) for chain sizes: 70 lb/ft (104.2 kg/m) **6**
- 14 inch (356 mm) for chain sizes: 80 lb/ft (119.1 kg/m), 100 lb/ft (148.8 kg/m) **7**
- 16 inch (406 mm) for chain sizes: 90 lb/ft (133.9 kg/m) **8**

C dimension

- 25 inch (635 mm) **AA**
- 26 inch (660 mm) **AB**
- 27 inch (686 mm) **AC**
- 28 inch (711 mm) **AD**
- 29 inch (737 mm) **AE**
- 30 inch (762 mm) **AF**
- 31 inch (787 mm) **AG**
- 32 inch (813 mm) **AH**
- 33 inch (838 mm) **AJ**
- 34 inch (864 mm) **AK**
- 35 inch (889 mm) **AL**
- 36 inch (914 mm) **AM**
- 37 inch (940 mm) **AN**
- 38 inch (965 mm) **AP**
- 39 inch (991 mm) **AQ**
- 40 inch (1 016 mm) **AR**
- 41 inch (1 041 mm) **AS**
- 42 inch (1 067 mm) **AT**
- 43 inch (1 092 mm) **AU**
- 44 inch (1 118 mm) **AV**
- 45 inch (1 143 mm) **AW**
- 46 inch (1 168 mm) **BA**
- 47 inch (1 194 mm) **BB**
- 48 inch (1 219 mm) **BC**
- 49 inch (1 245 mm) **BD**
- 50 inch (1 270 mm) **BE**
- 51 inch (1 295 mm) **BF**
- 52 inch (1 321 mm) **BG**
- 53 inch (1 346 mm) **BH**
- 54 inch (1 372 mm) **BJ**
- 55 inch (1 397 mm) **BK**

Milltronics test chain storage reels

Test chain storage reels are used to store roller test chains. All test chain storage reels come with a geared brake motor.

- 56 inch (1 422 mm)
- 57 inch (1 448 mm)
- 58 inch (1 473 mm)
- 59 inch (1 499 mm)
- 60 inch (1 524 mm)
- 61 inch (1 549 mm)
- 62 inch (1 575 mm)
- 63 inch (1 600 mm)
- 64 inch (1 626 mm)
- 65 inch (1 651 mm)
- 66 inch (1 676 mm)
- 67 inch (1 702 mm)
- 68 inch (1 727 mm)
- 69 inch (1 753 mm)
- 70 inch (1 778 mm)
- 71 inch (1 803 mm)
- 72 inch (1 829 mm)
- 73 inch (1 854 mm)
- 74 inch (1 880 mm)
- 75 inch (1 905 mm)
- 76 inch (1 930 mm)
- 77 inch (1 956 mm)
- 78 inch (1 981 mm)
- 79 inch (2 007 mm)
- 80 inch (2 032 mm)
- 81 inch (2 057 mm)
- 82 inch (2 083 mm)
- 83 inch (2 108 mm)
- 84 inch (2 134 mm)
- 85 inch (2 159 mm)
- 86 inch (2 184 mm)
- 87 inch (2 210 mm)
- 88 inch (2 235 mm)
- 89 inch (2 261 mm)
- 90 inch (2 286 mm)
- 91 inch (2 311 mm)
- 92 inch (2 337 mm)
- 93 inch (2 362 mm)
- 94 inch (2 388 mm)
- 95 inch (2 413 mm)
- 96 inch (2 438 mm)
- 97 inch (2 464 mm)
- 98 inch (2 489 mm)
- 99 inch (2 515 mm)
- 100 inch (2 540 mm)
- 101 inch (2 565 mm)
- 102 inch (2 591 mm)
- 103 inch (2 616 mm)
- 104 inch (2 642 mm)
- 105 inch (2 667 mm)

7MH7163-

- BL
- BM
- BN
- BP
- BQ
- BR
- BS
- BT
- BU
- BV
- BW
- CA
- CB
- CC
- CD
- CE
- CF
- CG
- CH
- CJ
- CK
- CL
- CM
- CN
- CP
- CQ
- CR
- CS
- CT
- CU
- CV
- CW
- DA
- DB
- DC
- DD
- DE
- DF
- DG
- DH
- DJ
- DK
- DL
- DM
- DN
- DP
- DQ
- DR
- DS
- DT

Milltronics test chain storage reels

Test chain storage reels are used to store roller test chains. All test chain storage reels come with a geared brake motor.

3 Phase motor voltage

- 230/460 V 60 Hz
- 200/400 V 50 Hz
- 575 V 60 Hz
- 190/380 V 50 Hz
- 190/380 V 60 Hz
- 220 V 60 Hz
- 415 V 50 Hz

Reel type

- Single compartment for 1 calibration test chain
- Double compartment for 2 calibration test chains

Reel diameter/motor mount location

- 36 inch (914 mm) / right hand access
- 42 inch (1 067 mm) / right hand access
- 48 inch (1 219 mm) / right hand access
- 60 inch (1 372 mm) / right hand access
- 36 inch (914 mm) / left hand access
- 42 inch (1 067 mm) / left hand access
- 48 inch (1 219 mm) / left hand access
- 60 inch (1 372 mm) / left hand access

Motor power

- 0.75 HP (0.56 kW)
- 1 HP (0.75 kW)
- 1.5 HP (1.12 kW)
- 2 HP (1.5 kW)
- 3 HP (2.24 kW)
- 5 HP (3.73 kW)
- 7.5 HP (5.59 kW)
- 10 HP (7.5 kW)
- 15 HP (11.19 kW)
- 20 HP (14.91 kW)

Operating instructions

- English
 - German
- Note: the operating instructions should be ordered as a separate item on the order.
- All literature is available to download for free, in a range of languages, at <http://www.siemens.com/processinstrumentation/documentation>
- This device is shipped with the Siemens Level and Weighing manual DVD containing the complete operating instructions library.

Accessories

- Local operator station: forward, reverse, e-stop, off/on
- Note: motor starter and voltage transformer required for use with controller, 120 V AC required for controller

7MH7163-

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 0
- 1
- 0
- 1
- 2
- 3
- 4
- 5
- 6
- 7
- A
- B
- C
- D
- E
- F
- G
- H
- J
- K

7ML1998-5JD01
7ML1998-5JD31

7MH7723-1JY