

**Selection and Ordering data**


Article No.

**SITRANS LU150**


Short-range integrated ultrasonic level transmitter, general purpose, 2-wire, 4 to 20 mA loop powered ideal for liquids, slurries, and bulk materials in open or closed vessels to 5 meters (16.4 feet)

➤ Click on the Article No. for the online configuration in the PIA Life Cycle Portal.


**7ML5201-****0 0****Transducer/Process connection (PVDF)**

PVDF copolymer, 2" NPT [(Taper), ANSI/ASME B1.20.1] 

**E**

PVDF copolymer, R 2" [(BSPT), EN 10226] 


**F**

PVDF copolymer, G 2" [(BSPP), EN ISO 228-1] 

**G**

PVDF copolymer, 4" Sanitary mounting


**J****Cable inlet**

M20 x 1.5 [General Purpose cable gland -20 ... +60 °C (-4 ... +140 °F) included] 

**B**

1/2" NPT stainless steel entry (no cable gland included)

**C**

◆ We can offer shorter delivery times for configurations designated with the Quick Ship Symbol . For details see page 9/5 in the appendix.

**Selection and Ordering data**

Order code

**Further designs**

Please add "-Z" to Article No. and specify Order code(s).

Stainless steel tag [13 x 45 mm (0.5 x 1.75 inch)]: Measuring-point number/ identification (max. 20 characters) specify in plain text

**Y15**

Test certificate: Manufacturer's test certificate M to DIN 55350, Part 18 and to ISO 9000

**C11****Operating Instructions**

English

Article No.

**A5E34590123**

Note: Operating instructions should be ordered as a separate line on the order

All literature is available to download for free, in a range of languages, at <http://www.siemens.com/processinstrumentation/documentation>

This device is shipped with the Siemens Level and Weighing manual DVD containing the ATEX Quick Start and Operating Instructions library.

**Accessories**

Tag, stainless steel, 12 x 45 mm (0.47 x 1.77 inch), one text line

**7ML1930-1AC**

Universal Box Bracket Mounting kit

**7ML1830-1BK**

Sanitary 4" mounting clamp

**7ML1830-1BR**

3" ASME, DN 65 PN 10, JIS 10K 3B ETFE Flange adapter for 2" NPT

**7ML1830-1BT**

3" ASME, DN 65 PN 10, JIS 10K 3B ETFE Flange adapter for 2" BSPT

**7ML1830-1BU**

2" NPT locknut, plastic

**7ML1830-1DT**

2" BSPT locknut, plastic

**7ML1830-1DQ**

Cable Gland - General Purpose -20 ... +60 °C (-4 ... +140 °F)

**A5E34457564**